BCS300

CEILING NETWORK STREAMING SPEAKER





The Bluesound Professional BCS300 PoE+ powered network active loudspeaker with integrated streaming capability is designed specifically for use in commercial installations. With built-in streaming and amplification, it efficiently delivers audio to its desired destination in a discreet and simplified manner. The player in the BCS300 is based on the established BluOS platform and is capable of playing and distributing content from local network storage as well as from a large number of streaming services, including some specifically designed for commercial use such as SoundMachine, Custom Channels, Qsic and SiriusXM Music for Business. As well as stand-alone use, it is possible to use a pair of BCS300 speakers in stereo configuration. Use of the BCS300 in a larger BluOS system is also possible, allowing for grouping into user-definable groups of whatever size is required with other BCS300 units and/or any other connected Bluesound Professional players on the network in an installation.

The BCS300 features a 3.5" LF driver and a 1" HF driver powered by a 23W high efficiency amplifier including a low power standby mode. The frequency response of the speaker is 45Hz to 20kHz and the THD+N of the system is 0.003% at full rated power. High efficiency electronics and drive units provide a maximum SPL of 102dB (using PoE+).

Control of the speaker can be accomplished by any Windows/Mac computer as well as any iOS/Android phone or tablet and the Bluesound Professional CP100 wall mount controller. Third party control is also possible with any of the leading systems. Security provisions prevent any unauthorized control of the system.

The PoE+ power supply makes this player easy to install in minutes with one Ethernet cable and eliminates the cost of providing an AC mains receptacle typical for all powered speakers.

FEATURES



- Full-range network streaming speaker system
- 3.5" LF driver and 1" HF driver
- 45Hz -20kHz frequency range
- 0.003% THD+N at full rated power
- Maximum SPL of 102db (PoE+)
- DSP providing equalization and other audio processing
- 2 x BCS300's can pair in stereo configuration
- Flexible and unlimited grouping of zones within a BluOS system
- Integration with local network content storage
- Integration with many streaming services including Custom Channels, SoundMachine, Qsic, SiriusXM Music for Business, Spotify, Tidal and Qobuz
- Integration with a wide variety of internet radio platforms

- PC/Mac, iOS/Android and third-party control
- Security preventing unauthorized control
- Specialist Bluesound Professional control panels
- Support of hi-res audio up to 192kHz/24 bit
- Support of MQA content
- Streaming via ethernet for increased reliability with PoE+ providing one-wire connectivity and power
- UL2043
- White magnetic grille included and optional black grille available
- Available in Black with White Grille
- Optional BCS Pendant Kit available in Black or White

ARCHITECTS & ENGINEERS SPECIFICATION

The network streaming speaker shall allow for the playing of material from network attached drives and a wide variety of streaming services including Custom Channels, SoundMachine, Qsic, SiriusXM Music for Business, Spotify, Tidal and Qobuz as well as internet radio platforms such as Tuneln and iHeart Radio. The network speaker shall support files up to 192kHz and 24-bit resolution as well as MQA encoded files. Control of the unit shall be possible from PC or Mac computers, Android and iOS mobile devices and third-party control systems. In addition, there shall be the provision for the connection of dedicated wall mount remote control panels to allow for local control of zones. The network speaker shall be based on the BluOS platform and shall be compatible with other BluOS devices to form a complete and integrated ecosystem including flexible grouping and control of zones. Networked speakers shall also be able to be paired in stereo combinations.


The network streaming speaker shall have a 3.5" woofer and 1" tweeter. The power amplifier shall be a high efficiency 23W unit with a maximum SPL of 102dB (using PoE+), built-in DSP for equalization and other audio processing. Streaming shall be via wired ethernet for increased reliability.


The unit shall have no controls to prevent unauthorized adjustment and control of the unit shall incorporate security to prevent unauthorized access via other devices. The power for this player shall be provided via PoE+.

The speaker shall be held in place with support dogs, and use a 152mm (6 ") cut out. Unit must be able to be transformed into a pendant format via accessory kit.

The network streaming speaker shall be the Bluesound Professional BCS300.







SPECIFICATIONS

CONNECTIVITY

Network

Power

User Interface

Environment Finish

AUDIO

Supported File Formats MP3, AAC, WMA, OGG, WMA-L, ALAC, OPUS

Hi-Res formats FLAC, MOA, WAV, AIFF

Native Sampling Rates 32-192KHZ 16-24 Bit Depths

PERFORMANCE

Free Internet Radio

Supported Cloud Services

-10db 45Hz-20kHz Frequency Response

THD+N-0.030% (20hz-20khz at Rated Power) Distortion

Power Output 23 Watts total system power at 0.030% THD

1x 89mm (3.5"), Woofer Speakers

Supported Operating Systems 1x 25mm (1"), Tweeter Plaus music from network shares on the

following desktop operating systems: Microsoft Windows 2000 and newer and Apple Macintosh 7 and newer.

Tuneln Radio, iHeartRadio, Calm Radio, Radio

Paradise, LiveXLive

SoundMachine, Tunify, Custom Channels, SiriusXM for Business, Spotify, Tidal, Amazon, Deezer, Qobuz, Tuneln, Radio.com and many

Integration Partners Control4, RTI, Crestron, URC, QSYS, push,

ELAN, Lutron

marks of their respective owners. *Some features will be available via a future software update. 20-087

JPG Album Art

USER INTERFACE Mobile Operating System BluOS-Free Android and IOS App Available Online at Google Play and Apple App Store GENERAL Processor ARM® CORTEX™ A53 1.8GHz Unit Weight 123kg/2.7lb 182mm (7.1") DIA x 126mm(4.9") H Gross Dimensions 152 mm (6") cut out required Cutout Dimension 152mm (6 inch) diameter -10°C to 50° C, 20% to 80% relative humidity (Idle) Storage

Ethernet RJ45, 100BaseT

PoE+ IEEE 802.3 at Type 2-30W

Available in Black with White Grille

Safety UL2043

© Bluesound International, Bluesound Professional, Bluesound, the stylized wordmark and "B" logotype, the phrase "HiFi for a wireless generation", and all other Bluesound product names and taglines are trademarks or registered trademarks of Bluesound International, a division of Lenbrook Industries Limited. All other logos and services are trademarks or service