




TECHNICAL DATASHEET



The RX1260A is a 360° omnidirectional acoustic device with a coverage radius of 1,392 meters and a notification area spanning 6.09 km². It is ideal for large-scale area broadcasting and alarm notifications in major venues, making it suitable for environments such as islands, forests, grasslands, and airports. Equipped with a TCP/IP network interface, the device supports remote control and management, meeting the operational requirements of scenarios like mass notification.

Features


- 360° uniform coverage
- 1 to 24 cells configuration
- Live-voice message/build-in warning tone/mp3
- TCP/IP or local control unit
- Easy operation/maintenance
- Aluminium alloy
- All-weather use
- IP65

Acoustic Specifications

Parameter	Details
Peak SPL@1m	150dBA
Continuous SPL@1m	144dBA
Continuous SPL@30m	114dBA
Notification Radius	1392m
Notification Area	6.09km²
Frequency Response	250Hz~7000Hz

Mechanical Specifications

Parameter	Details
Dimension(D*H)	700mm*1300mm
Weight	85kg
IP Rating	IP65



Electrical Specifications

Parameter	Details
Rated Power	2400W
Operating Voltage	110V~260V AC
Communication Method	TCP/IP

Environmental Specifications

Parameter	Details
Hot Operating Temp	MIL-STD-810H, 501.7 High Temperature,Procedure II,Design type Hot, 50°C
Cold Operating Temp	MIL-STD-810H, 502.7 Low Pressure, Procedure II,Design type Basic Cold, -40°C
Hot Storage Temp	MIL-STD-810H, 501.7 High Temperature,Procedure I,60°C
Cold Storage Temp	MIL-STD-810H, 502.7 Low Pressure, Procedure I,-50°C
Operating Humidity	MIL-STD-810H, 507.6 Humidity,Procedure II - Aggravated
Rain	MIL-STD-810H, 506.6 Rain,Procedure I - Rain and Blowing Rain

OPTIONAL ACCESSORIES



★ Column



★ Solar Panel



★ Spare Battery



★ Controller



★ Controller

Beijing Ribri Technology Co., Ltd.



Add: 1802, 18th Floor, Building 3, No.8 Chama Street, Xicheng District, Beijing

Email: market@ribri.com

Whatsapp: +86 13911896601

Website: www.ribri.com