

winp^oint

Directional Sound System

WP-2830A



DIRECT
THE
SOUND

ENJOY
THE
SILENCE



WP-2830A DIRECTIONAL SPEAKER TECHNICAL SPECIFICATIONS

Audio Input	USB Disk	FAT/FAT32 (MP3 and WAV audio file formats)
	MicroSD Card	FAT/FAT32 (MP3 and WAV audio file formats)
	Aux Input	3.5mm Connector, Max. Signal 150mV _{RMS}
	Bluetooth	Bluetooth v4.2
Audio Output	Frequency Response	200Hz - 18kHz
	Power	85dB @1kHz/1m
	Distance	Up to 100m ⁽¹⁾
Visual Notification	Type	Red LED
	Dimension	Diameter 5mm
Remote Control	Operating Distance	Up to 5m ⁽²⁾
	Battery	3V CR2025
Target Laser	Operating Distance	5mW Red
	Disatance	Up to 30m ⁽³⁾
Power Adapter	Input	85-264 VAC, 50/60 Hz (Standard Grounded Socket)
	Output	24 VDC-1A (P1J DC Connector)
	Consumption	15 W (max.)
Ambient Conditions	Operation Temperature	-10°C to 60°C
	Storage Temperature	-25°C to 85°C
	Humidity	<95% RTH
Mechanical	Dimensions	300 mm x 280 mm x 35 mm (W x H x D)
	Weight	1460 g
	Material	Aluminum (Body), Steel (Front Panel)
	Mounting	VESA 100 Mount Apparatus (Optional)
	Color	Black

(1) Audible sound level may vary depending on the ambient noise level and environmental conditions.

(2) Remote control operating distance may vary depending on the angle with the receiver, obstacles in the environment and battery level.

(3) Visibility of marking laser may vary depending on the intensity of other light sources in the environment.