

FAMA 8

Two-way 8" ceiling loudspeaker

Ceiling loudspeaker for 100 V line and 16 Ω low-impedance installations. Power 60 W at 16 Ω , max. 30 W on a 100 V line. Sensitivity 89 dB, frequency response 50 Hz - 20 kHz. Low-profile magnetic frameless grille, adjustable tweeter and switchable high-frequency correction.

60 W / 16 Ω

30 W / 100 V

8" + 1"

cut-out $\varnothing$ 258 mm

Key features

Two-way design

8" woofer and adjustable 1" tweeter. Frequency response 50 Hz - 20 kHz, sensitivity 89 dB.

High-frequency correction

-3/0/+3 dB switch accessible under the grille, also after installation.

Choice of grilles

White round grille as standard. Optional white square, black round or black square grilles.

Discreet appearance

Low-profile, magnetic, frameless grille.

100 V line or 16 Ω

100 V line: transformer taps 7.5 / 15 / 30 W, max. 30 W. Without transformer at 16 Ω : rated power 60 W.

Any RAL colour

Optionally, the grille can be painted in any colour from the RAL palette.

Recommended for

background music systems

paging systems

restaurants and bars

hotels

conference and training rooms

Specifications

Rated power (16 Ω , without transformer)	60 W
Max. power on 100 V line	30 W
Transformer taps (100 V)	7.5 W / 15 W / 30 W
Impedance without transformer	16 Ω
Speaker line voltage	100 V
Sensitivity	89 dB
Switchable high-frequency correction	-3/0/+3 dB, accessible after installation
Frequency response	50 Hz - 20 kHz
Drivers	8" woofer, 1" tweeter
Speaker dimensions	284x105 mm
Cut-out diameter	$\varnothing$ 258 mm
Mounting depth	105 mm
Weight	2.4 kg

Installation

- cut-out $\varnothing$ 258 mm
- mounting depth 105 mm
- high-frequency correction accessible under the grille after installation

Grilles




White round
standard



White square
option



Black round
option



Black square
option

- standard: white round grille
- optional: white square, black round or black square
- the grille can be painted in any RAL colour